

S/N 10/674,112

Response to Office Action Dated 09/13/2005

**MODIFICATIONS TO CLAIM STATUS**

As seen infra, the Applicant hereby elects, with traverse, Group I, comprising claims 1—12.

By way of overview, claims 1—37 are currently pending. Of these pending  
5 claims:

- A) Claims 1—12 remain in their original form;
- B) Claims 13—37 are currently withdrawn.

**Listing of Claims**

- 10        1.        (original) An ink drying system for a printer, comprising:  
an IR heating element;  
a guide, to concentrate heat energy from the IR heating element on print  
media; and  
a controller procedure to control operation of the IR heating element.
- 15        2.        (original) The system of claim 1, additionally comprising:  
sensors, in communication with the controller procedure, to measure  
relative humidity and temperature.
- 20        3.        (original) The system of claim 1, wherein the controller procedure  
additionally considers print data as a constraint to control operation of the IR  
heating element.

S/N 10/674,112

Response to Office Action Dated 09/13/2005

4. (original) The system of claim 1, wherein the controller procedure causes the IR heating element to put out more heat in locations on the print media where print data indicate extensive use of ink than in locations where the print data indicate moderate use of ink.

5

5. (original) The system of claim 1, wherein the IR heating element is located on a print carriage.

6. (original) The system of claim 1, wherein IR heating elements are located on both sides of a printhead carried by a print carriage.

7. (original) The system of claim 1, wherein the guide comprises:  
a light pipe, carried by a carriage and configured to direct IR energy toward print media adjacent to a printhead carried by the carriage, wherein the light pipe comprises: a collector; a pipe, in communication with the collector, and an emitter, in communication with the pipe.

8. (original) The system of claim 1, wherein the guide comprises:  
a reflector to direct IR energy to print media adjacent to a printhead.

20

S/N 10/674,112

Response to Office Action Dated 09/13/2005

9. (original) The system of claim 1, wherein the guide comprises:  
a collimator to direct IR energy in a substantially straight line, substantially  
parallel to a carriage rod upon which a printhead travels; and  
a light pipe, movable along a carriage supporting the printhead, to receive  
5 IR energy from the collimator and to deliver IR energy to print media adjacent to  
the printhead.

10. (original) The system of claim 1, additionally comprising:  
wherein first and second guides are configured for operation in first and  
10 second directions of printhead movement.

11. (original) The system of claim 1, wherein the guide comprises:  
a page wide array of IR heating elements and guides; and  
wherein the page wide array is located in a forward position, configured to  
15 warm print media prior to application of ink.

12. (original) The system of claim 1, wherein the guide comprises:  
a page wide array of IR heating elements and guides; and  
wherein the page wide array is located in a rearward position, configured to  
20 warm print media after application of ink.

S/N 10/674,112

Response to Office Action Dated 09/13/2005

13. (withdrawn) A processor-readable medium comprising processor-executable instructions for operating a printer, the processor-executable instructions comprising instructions for:

- 5       moving a printhead relative to print media; and  
operating an IR lamp to direct IR energy according to a guide, wherein the guide is configured for directing the IR energy toward the print media.

14. (withdrawn) A processor-readable medium as recited in claim 13,  
10       wherein operating the IR lamp comprises:

evaluating print data to determine timing and level of IR energy needed to dry the print media.

15. (withdrawn) A processor-readable medium as recited in claim 13,  
15       comprising further instructions for:

moving a second printhead over an area of the print media already printed by the printhead and heated by the IR lamp.

16. (withdrawn) A processor-readable medium as recited in claim 13,  
20       wherein directing the IR energy toward the print media comprises:

generating IR directed toward a collector portion of a light pipe for movement out an emitter portion of the light pipe and contact with a desired location on the print media.

S/N 10/674,112

Response to Office Action Dated 09/13/2005

17. (withdrawn) A processor-readable medium as recited in claim 13, wherein operating the IR lamp releases IR energy is tuned to emphasize wave lengths selected for absorption by water.

5 18. (withdrawn) A processor-readable medium as recited in claim 13, wherein operating the IR lamp additionally comprises evaluating ambient temperature and humidity to determine timing and level of IR energy needed to dry the print media.

10 19. (withdrawn) A processor-readable medium as recited in claim 13, wherein moving the printhead relative to the print media comprises moving a carriage carrying a printhead on a carriage rod, and wherein operating the IR lamp causes IR energy to be sent through a compound guide, comprising a collimating portion adjacent to the IR lamp and a light pipe carried by the printhead.

15

20. (withdrawn) A print system, comprising:

means for generating IR energy comprising frequencies calculated for absorption by water;

means for directing the IR energy through operation of a guide for  
20 concentration on print media; and

means for using ambient temperature and humidity to assist in controlling operation of the means for generating IR energy.

S/N 10/674,112

Response to Office Action Dated 09/13/2005

21. (withdrawn) The print system of claim 20, wherein the means for directing comprises a light pipe having a collector in communication with the means for generating IR energy and an emitter to concentrate the IR energy on a desired location on the media.

5

22. (withdrawn) The print system of claim 20, additionally comprising:  
means for using print data to assist in controlling operation of the means for generating IR energy.

10

23. (withdrawn) The print system of claim 20, additionally comprising:  
means for using print data to cause more IR energy to be used in response to more printed pixels and less IR energy to be used in response to less printed pixels.

15

24. (withdrawn) The print system of claim 20, additionally comprising:  
means for using print data to turn on and off the means for generating IR energy in response to operation and non-operation of a printhead.

20

25. (withdrawn) The print system of claim 20, additionally comprising:  
means for providing proportional amounts of ink and IR energy, in view of an ambient temperature and humidity, on locations of the print media.

S/N 10/674,112

Response to Office Action Dated 09/13/2005

26. (withdrawn) The print system of claim 20, wherein the guide comprises:

means for collimating the IR energy; and

5 means for receiving the collimated IR energy with a light pipe carried by a printhead, and for directing the IR energy to contact print media.

27. (withdrawn) The print system of claim 20, wherein the guide comprises:

means for reflecting IR energy to contact print media.

10

28. (withdrawn) The print system of claim 20, wherein the guide comprises:

means for piping IR energy through an IR fiber optic material to heat a location on print media; and

15 means for timing the heating of the location on the print media to coordinate with application of ink to the location on the print media.

29. (withdrawn) A method of drying ink, comprising:

20 controlling operation of an IR lamp to generate IR energy, wherein the IR energy is of a wave length calculated for absorption by water, and wherein the IR energy is generated in response to anticipation of ink on print media;

reflecting the IR energy into a guide; and

directing the IR energy to the print media through the guide.

S/N 10/674,112

Response to Office Action Dated 09/13/2005

30. (withdrawn) The method of claim 29, wherein the anticipation is based on reviewing print data.

31. (withdrawn) The method of claim 29, wherein controlling operation  
5 of the IR lamp to generate a level of IR energy comprises:  
measuring ambient temperature and humidity; and  
generating the level of IR energy proportional to the ambient temperature  
and humidity.

10 32. (withdrawn) The method of claim 29, wherein directing the IR  
energy to print media through the guide comprises guiding the IR energy is  
through collector, pipe and emitter portions of the guide.

33. (withdrawn) The method of claim 29, directing the IR energy to  
15 print media through the guide comprises:  
directing the reflected IR energy through a collimating device;  
receiving collimated IR energy in a light pipe; and  
directing the IR energy to print media using the light pipe.



S/N 10/674,112

Response to Office Action Dated 09/13/2005

34. (withdrawn) A processor-readable medium comprising processor-executable instructions for operating a printer, the processor-executable instructions comprising instructions for:

operating an IR lamp to generate a quantity of IR energy;

5 selecting the quantity of the IR energy generated to be proportional to ink to be used, as indicated by print data; and

using ambient temperature and humidity to assist in controlling operation of the IR lamp.

10 35. (withdrawn) The processor-readable medium of claim 34, wherein selecting the quantity of the IR energy generated comprises instructions for:

increasing the quantity of IR energy where ink density is higher and decreasing the quantity of IR energy where ink density is lower, as indicated by the print data.

15

36. (withdrawn) The processor-readable medium of claim 34, wherein selecting the quantity of the IR energy generated comprises instructions for:

turning on and off the IR lamp in response to operation and non-operation of a printhead.

20

37. (withdrawn) The processor-readable medium of claim 34, wherein selecting the quantity of the IR energy generated comprises instructions for:

selecting the level of IR energy based on measured ambient temperature and humidity.